


DA-2Y(St)H 4*2*AWG24/1



1. Category: 5

2. Construction: see figures

- 1) Conductor: bare copper wire, AWG 24/1
- 2) Insulation: solid PE
Color code: white (blue)/blue, white (orange)/orange, white (green)/green, white (brown)/brown
- 3) Pair: 4 twisted pairs
- 4) Tape: Polyester
- 5) Screen: single-side composite aluminum and plastic foil
- 6) Drain wire: 0.5mm tinned copper
- 7) Outer sheath: LSOH (green; RAL 6017)



3. Electronic characteristics at 20°C:

DC resistance (max.)	93.5 Ohm/km
Insulation resistance (min.)	5 Gohm x km
Mutual capacitance (app.)	52 nF/km
Transfer capacitance [e] (app.)	1500 pF/km
Signal velocity [c] (app.)	0.64
Propagation Delay (app.)	515 ns/100m
Skew at 100 MHz (app.)	35 ns/100m
Characteristic impedance at 100 MHz	100±5 Ohm
Test voltage Ueff	1.000 V
Operating voltage Ueff (max)	125 V

Frequency MHz	Attenuation dB/100m	NEXT dB	PS-NEXT dB/100	EL-FEXT dB/100m	PS-ELFEXT dB/100m	RL dB/100m
	max	min	min	min	min	min
1	2.1	62.3	62.3	60.8	60.8	23.1
4	4.0	53.3	53.3	48.8	48.8	24.5
10	6.3	47.3	47.3	40.8	40.8	25
16	8.0	44.3	44.2	36.7	36.7	25
20	9.0	42.8	42.8	34.8	34.8	25
31.25	11.4	39.9	39.9	30.9	30.9	23.6
62.5	16.5	35.4	35.4	24.9	24.9	21.5
100	21.3	32.3	32.3	20.8	20.8	20.1

EN 50173

ISO/IEC 11801:2002(E)

IEC61156-5

YD/T1019-2001

4. Fire behavior:

Fire retardant:	IEC 60332-1-2
Halogenic acid gas emission:	IEC60754-1/2
Smoke density:	IEC61034-1/2

5. Performance (Type and bandwidth of cables)

Acc. to EN 50173 and ISO/IEC 11801:2002(E)/ IEC61156/ YD/T1019-2001

Bandwidth: 100 MHz

6. Application

Installation cable for generic cabling systems acc. to ISO/IEC 11801 and EN 50173 (2.edition)

Ideal for all applications of Class D (Video, Data, Voice) upto 1GBE, acc. to IEEE802.3 ab, VoIP, PoE

7. Mechanical characteristic:

Bending radius:

During installation: 8*cable diameter

After installation: 4*cable diameter

Tensile strength (Max.): 100N

Crush: 1000 N/100mm

Impact (numbers of shocks): 10

8. Electromagnetic behavior:

Transfer impedance at 10MHz: 100 mOhm/m

Screen attenuation upto 100MHz: 40 db

Coupling attenuation upto 1000MHz: 35 db

9. Chemical property:

Thermal characteristics:

Temperature range for fixed installation: -20°C to +60°C

Temperature range for mobile installation: 0°C to + 50°C

10. Dimensions:

Type	Size	Out diameter(mm)	Weight (kg/km)	Cu Index (kg/km)	Sheath Color
DA-2Y(St)H 4x2xAWG 24/1	4P	6.4	39 (approx)	18,4 (approx)	green RAL6017

11. Package:

305m/box,
500m/drum,
1000m/drum

12. Article number:

DA-221041-000